

Linea



Milan

Linea

La sencilla idea de enmarcar la luz es la naturaleza de este plafón. Compuesta de una pantalla difusora de vidrio y un marco de aluminio extrusionado con detalladas uniones.

Enmarcando la luz

Diseño / Design: Jordi Jané Variantes: Aluminio cepillado, Lacado blanco mate
Variations: Brushed aluminium, Matt white lacquering (RAL 9016)

Linea



REF: 6912

Linea



REF: 6500

Linea


Framing light

The simple idea of framing light is the essence of this ceiling light. Linea comprises a glass diffuser shade and an extruded aluminum frame with detailing.

Linea

MLN Linea

Linea 500 C.



Datos técnicos Technical data




300 x 300 mm | H. 75 mm
1 x PCB LED 17 W
1650 lumens | 2.700 K | CRI 90
Dimable | Dimmable
Clase I: Aislamiento básico
Class I: Basic insulation

Código Code

6910 ● Lacado blanco / Matt white lacquering (RAL 9016)
6499 ● Aluminio anodizado/ Brushed aluminium

Acabados Finishes

Linea 500 C.



Datos técnicos Technical data




370 x 370 mm | H. 75 mm
1 x PCB LED 17 W
1650 lumens | 2.700 K | CRI 90
Dimable | Dimmable
Clase I: Aislamiento básico
Class I: Basic insulation

Código Code

6911 ● Lacado blanco / Matt white lacquering (RAL 9016)
6500 ● Aluminio anodizado/ Brushed aluminium

Acabados Finishes

Linea 500 C.



Datos técnicos Technical data



420 x 420 mm | H. 75 mm
1 x PCB LED 29 W
2580 lumens | 2.700 K | CRI 90
Dimable | Dimmable
Clase I: Aislamiento básico
Class I: Basic insulation

Código Code

6912 ● Lacado blanco / Matt white lacquering (RAL 9016)
6501 ● Aluminio anodizado/ Brushed aluminium

Acabados Finishes

Características

Pantalla difusora de vidrio óptico de 4 mm de grosor, satinado al ácido. Marco en aluminio extrusionado con uniones en aluminio inyectado. Acabados en aluminio satinado cepillado y lacado blanco mate (RAL 9016). Fijación del marco a la base mediante tornillos en acero inoxidable. Base de fijación al techo en acero estampado, lacado blanco mate (RAL 9016) y lacado gris metalizado (similar al RAL 9006 mate).

Properties

Diffusing shade in optic, acid-etched glass 4 mm thickness. Frame in extruded aluminium with injected aluminium joints. Finishing in satin brushed aluminium and matt white lacquer (RAL 9016). Fixing of the frame to the base through stainless steel screws. Fixing base in stamped steel, lacquered matt white (RAL 9016) and lacquered grey metal (similar to RAL 9006 matt).

